

COMMERCIAL 21 X-SERIES

| Model Number | Engine | Controls | Size | Curb Weight | Length with Handle | Height with handle ¹ | Width | Price |
|----------------|---------------------|---------------------|------|-------------|--------------------|---------------------------------|-------|-------|
| ECX180CKA21000 | FJ180V Kawasaki KAI | Self-Propelled Zone | 21" | 123 lbs. | 62.0" | 38.0" | 22.0" | \$ |
| ECX160CHN21000 | GXV160 Honda | Self-Propelled Zone | 21" | 112 lbs. | 62.0" | 38.0" | 22.0" | \$ |
| ECX180CKA210BC | FJ180V Kawasaki KAI | Self-Propelled BBC | 21" | 123 lbs. | 62.0" | 38.0" | 22.0" | \$ |

QUICK REFERENCE

| WHEELS | Front | | Drive | BELTS | | |
|--------|---------------|----------|----------|-------|----------|-----|
| | 9" (standard) | 126-7347 | 135-0203 | Drive | 109-7299 | BBC |

| BLADES ² (QTY) | 21"(1) | CABLES | |
|---------------------------|-----------------|-----------------|----------|
| High Lift Solid | 142-6457 | Zone (Honda) | 116-4443 |
| Extreme 2 | 133-8182 | Zone (Kawasaki) | 116-0905 |
| Low-Lift | 133-8183 | BBC | 116-0901 |
| Medium/Mulch | 135-0413 | Drive | 126-7397 |
| Mulching | 116-5005 | Throttle | 116-4424 |

¹varies with 0.5" cutting selections.

²material is 0.135" thick alloy steel austempered to RC 38-44

KEY FEATURES

- Commercial performance and durability.
- 5"-deep cutting deck provides Exmark® signature cut and superior performance whether bagging or mulching.
- Innovative and durable front height adjustment replacing traditional pivot style adjusters.
- Single-point rear height adjustment allows operator to quickly change cutting height.
- Blade Brake Clutch (BBC) enables operator to disengage blades without shutting down the engine.
- Front engine guard protects valve cover and head gasket from being damaged on trailers and helps when lifting.
- Formed, steel-wear plates, are strategically placed on the edges of the cutting deck to ensure that the deck is not damaged from impacts and abrasions.
- Drive and OPC bails are foam-coated to minimize vibration and fatigue.
- Mulch plug and rear door handle standard.
- See page 157 for Exmark® warranty details

ACCESSORIES & ATTACHMENTS

No Accessories Available

SPECIFICATIONS

Engine – FJ180V Kawasaki KAI engine governed to 3,300 rpm; GXV160 Honda engine governed to 3,300 rpm.

Air Filter – Dual element air cleaner.

Engine Deck – 5"-deep, 1/4"-thick die-cast aluminum.

Drive System – Self-propelled; rear-wheel gear-driven.

Transmission – Infinitely variable speed selection, dual wheel drive.

Speed – 0.0 mph to 4.2 mph (6.8 kmph) forward.

Speed Control – Fingertip control.

Fuel Capacity – 1 gallon (3.8-L).

Style – Fixed-deck, rear-discharge bagger and mulch plug standard.

Width Available – 21" (53.3 cm).

Cutting Height – 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Blade-Tip Speed – Approximately 18,500 fpm.

Blades – 1 blade at 20.5".

Drive Tires – 9" x 2.5", semi-pneumatic.

Safety Package – Zone start/Blade Brake Clutch (BBC).

Bag Capacity – 2.5 bushels (20 gallons).

