

COMMERCIAL 30 X-SERIES

Model Number	Engine	Controls	Size	Curb Weight	Length with Handle ²	Height with handle ²	Width	Price
ECX180CKA30000	FJ180V Kawasaki KAI	Self-propelled	30"	185 lbs.	68.0"	38.25"	31.9"	\$
ECX200CKC30000	CV200 Kohler	Self-propelled	30"	185 lbs.	68.0"	38.25"	31.9"	\$

²With handle in medium position. Varies with 0.5" cutting selections.

QUICK REFERENCE

BLADES (QTY)	30"(2)
High-Lift Notched	142-6456
High-Lift Solid	142-4736
Low-Lift	142-6455

BELTS	30"	CABLES	30"
Transmission	133-8151	Drive	137-4807
Blade Clutch	121-5765	BBC	137-4759
Blade Drive	120-3335	Brake	138-5399

KEY FEATURES

- Improve productivity, increase control and manage costs with a deceptively light walk-behind mower.
- Positive drive transmission holds side-hills and helps prevent downhill "run-away".
- Unit weighs more than a 21", but operator will not see additional fatigue in operation due to balance of unit and increased coverage.
- Innovative and durable front height adjustment replacing traditional pivot style adjusters.
- Single-point rear height adjustment allows operator to quickly change cutting height.
- Self-tensioning belt drive to transmission – eliminates need for service adjustments and prolongs belt life.
- Welded steel cutting deck - constructed with 1/2" dia. side wear bars and 1" dia. bumper to protect front end and deck with metal side discharge cover.
- Handle bar, lever actuated park brake - disengaged with drive control bail.
- See page 157 for Exmark® warranty details



ACCESSORIES & ATTACHMENTS

Micro-Mulch 116-8841

For more information on Accessories see page 112-151

SPECIFICATIONS

Engine – CV200 Kohler engine; FJ180V Kawasaki KAI engine; governed to 3,500 rpm.

Air Filter – Quad-clean air cleaner.

Engine Deck – 4.6"-deep stamped steel with welded reinforcement.

Drive System – Self-propelled, rear-wheel gear-driven.

Transmission – Infinitely variable speed selection.

Speed – 0.0 mph to 3.8 (6.1 kmph) mph forward.

Speed Control – Finger-tip control.

Fuel Capacity – 1 gallon (3.8-L) fuel tank.

Style – Fixed-deck. Ability to rear bag, side-discharge or mulch.

Width Available – 30" (76 cm).

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.5" (1.3 cm) increments.

Blade-Tip Speed – Approximately 18,500 fpm.

Blades – 2 blades at 15.4".

Front Tires – 9 x 2.4, semi-pneumatic.

Drive Tires – 10.5 x 3.0, semi-pneumatic.

Safety Package – Blade Brake Clutch (BBC).

Park Brake - Disc type.

Bag Capacity – 2.5 bushels (20 gallons).